

Input Voltage (VRMS) ($\pm 10\%$) See Table
 Frequency Range (KHz) See Table
 Output Power 60VA
 % Ripple** 5%
 Efficiency** 90%
 Temperature Class 130°C
 Ambient Temperature Range -40°C to +85°C
 Temperature Rise** 15°C

Primary Inductance (mH) Typical: See Table
 Dielectric Strength Tested: 8KVrms @60Hz.
 Primary and Shield to all Secondaries
 Partial Discharge (Corona) Tested: 4KVrms @60Hz.
 Primary and Shield to all Secondaries
 BIL Rating: 15KV

**Approximate values (Contact us for defined limits)

Configuration Number	Schematic	Primary			Secondary
		Input (Vrms)	Inductance (mH—Typ.)	Frequency Range KHz	Output (Vrms) @Arms
BB4000-36-18-18	1A/1B	36	1.92	10-50	18.0 @ 3.333
BB4000-36-18-0	2A/2B				18.0 @ 3.333
BB4000-36-18-0	3A/3B				18.0 @ 3.333
BB4000-48-18-18	1A/1B	48	2.28		18.0 @ 3.333
BB4000-48-18-0	2A/2B				18.0 @ 3.333
BB4000-48-18-0	3A/3B				18.0 @ 3.333
BB4000-100-18-18	1A/1B	100	3.10		18.0 @ 3.333
BB4000-100-18-0	2A/2B				18.0 @ 3.333
BB4000-100-18-0	3A/3B				18.0 @ 3.333
BB4001-36-18-18	1A/1B	36	0.64	50-100	18.0 @ 3.333
BB4001-36-18-0	2A/2B				18.0 @ 3.333
BB4001-36-18-0	3A/3B				18.0 @ 3.333
BB4001-48-18-18	1A/1B	48	0.70		18.0 @ 3.333
BB4001-48-18-0	2A/2B				18.0 @ 3.333
BB4001-48-18-0	3A/3B				18.0 @ 3.333
BB4001-100-18-18	1A/1B	100	1.03		18.0 @ 3.333
BB4001-100-18-0	2A/2B				18.0 @ 3.333
BB4001-100-18-0	3A/3B				18.0 @ 3.333
BB4002-36-18-18	1A/1B	36	0.32	100-250	18.0 @ 3.333
BB4002-36-18-0	2A/2B				18.0 @ 3.333
BB4002-36-18-0	3A/3B				18.0 @ 3.333
BB4002-48-18-18	1A/1B	48	0.38		18.0 @ 3.333
BB4002-48-18-0	2A/2B				18.0 @ 3.333
BB4002-48-18-0	3A/3B				18.0 @ 3.333
BB4002-100-18-18	1A/1B	100	0.60		18.0 @ 3.333
BB4002-100-18-0	2A/2B				18.0 @ 3.333
BB4002-100-18-0	3A/3B				18.0 @ 3.333

