

Input Voltage (VRMS) ($\pm 10\%$) See Table
 Frequency Range (KHz) See Table
 Output Power 10VA
 Regulation** 4.0 %
 Efficiency** 85 %
 Temperature Class 130°C
 Ambient Temperature Range -40°C to +85°C
 Temperature Rise** 10°C

Primary Inductance (mH) Typical: See Table
 Coupling Capacitance (pF) Maximum See Table
 Leakage Inductance** (mH) Nominal See Table
 Dielectric Strength Tested: 5500Vrms @60Hz.
 Primary and Shield to all Secondaries
 Partial Discharge (Corona) Tested: 2000Vrms @60Hz.
 Primary and Shield to all Secondaries
 BIL Rating: 3000V
 **Approximate values (Contact us for defined limits)

Configuration Number	Schematic	Primary			Secondary	
		Input (Vrms)	Inductance (mH—Typ.)	Frequency Range KHz	Output (Vrms) @Arms	
					Secondary 1	Secondary 2
IN1000-36-18-18	1A/1B	36	2.50	10-50	18.0 @ 0.278	18.0 @ 0.278
IN1000-36-18-0	2A/2B				18.0 @ 0.556	
IN1000-36-18-0	3A/3B				18.0 @ 0.556	
IN1000-48-18-18	1A/1B	48	4.50		18.0 @ 0.278	18.0 @ 0.278
IN1000-48-18-0	2A/2B				18.0 @ 0.556	
IN1000-48-18-0	3A/3B				18.0 @ 0.556	
IN1000-100-18-18	1A/1B	100	13.30		18.0 @ 0.278	18.0 @ 0.278
IN1000-100-18-0	2A/2B				18.0 @ 0.556	
IN1000-100-18-0	3A/3B				18.0 @ 0.556	
IN1001-36-18-18	1A/1B	36	0.90	50-100	18.0 @ 0.278	18.0 @ 0.278
IN1001-36-18-0	2A/2B				18.0 @ 0.556	
IN1001-36-18-0	3A/3B				18.0 @ 0.556	
IN1001-48-18-18	1A/1B	48	1.10		18.0 @ 0.278	18.0 @ 0.278
IN1001-48-18-0	2A/2B				18.0 @ 0.556	
IN1001-48-18-0	3A/3B				18.0 @ 0.556	
IN1001-100-18-0	1A/1B	100	2.20		18.0 @ 0.278	18.0 @ 0.278
IN1001-100-18-0	2A/2B				18.0 @ 0.556	
IN1001-100-18-0	3A/3B				18.0 @ 0.556	
IN1002-36-18-18	1A/1B	36	0.60	100-250	18.0 @ 0.278	18.0 @ 0.278
IN1002-36-18-0	2A/2B				18.0 @ 0.556	
IN1002-36-18-0	3A/3B				18.0 @ 0.556	
IN1002-48-18-18	1A/1B	48	0.70		18.0 @ 0.278	18.0 @ 0.278
IN1002-48-18-0	2A/2B				18.0 @ 0.556	
IN1002-48-18-0	3A/3B				18.0 @ 0.556	
IN1002-100-18-18	1A/1B	100	1.00		18.0 @ 0.278	18.0 @ 0.278
IN1002-100-18-0	2A/2B				18.0 @ 0.556	
IN1002-100-18-0	3A/3B				18.0 @ 0.556	

IN1000 Parasitic Values

Frequency KHz	Voltage RMS	Leakage Inductance μH (Typ.)	Capacitance pF (Typ.)
10 - 50	36	15	20
	48	20	25
	100	30	30
50 - 100	36	12	15
	48	15	20
	100	25	25
100 - 250	36	10	10
	48	12	15
	100	15	20

